

zrcadla s LED osvětlením **NIKA LED**

TECHNICKÉ DATA

Typ	Barevná teplota (K)	Světelný tok (lm)	Spotřeba el. energie (W)	Energetická třída	Napájení	Stupeň krytí	Rozměry (mm)
1/60	6300	255	8,8	A++	AC 230V-50Hz / DC 12V	IP21	600x650x30
1/80			10,0				800x650x30
1/100			11,0				1000x650x30
1/120			13,4				1200x650x30
2/60	6300	577	11,6	A	AC 230V-50Hz / DC 12V	IP21	600x650x30
2/80							800x650x30
2/100							1000x650x30
3/60	6300	577	11,6	A	AC 230V-50Hz / DC 12V	IP21	600x650x30
3/80			13,4				800x650x30
3/100			15,0				1000x650x30
3/120			17,1				1200x650x30
4/60	6300	577	27,5	A	AC 230V-50Hz / DC 12V	IP21	600x650x30
4/80			30,0				800x650x30
4/100			30,0				1000x650x30
4/120			23,9				1200x650x30
6/60	4000	255	8,7	A	AC 230V-50Hz / DC 12V	IP21	600x650x30
6/80			9,1				800x650x30
6/100			11,1				1000x650x30
7/60	6300	255	5,1	A	AC 230V-50Hz / DC 12V	IP21	600x650x30
7/80			5,9				800x650x30
7/100			6,4				1000x650x30
10/60	6300	255	6,6	A	AC 230V-50Hz / DC 12V	IP21	∅ 600x30
10/60 TS			6,6				∅ 600x30
10/80			8,4				∅ 800x30
10/80 TS			8,4				∅ 800x30